Product

BROCHURE

CASSA





Jl. Kyai Caringin No.20B Jakarta 10150, telp: 021 63863334, 021 6308338 Jl. Gajah Mada no.170 Jakarta 11130, telp: 021 6594870, 021 6590263 www. persindo.co.id - email: sales@persindo.co.id



Body

: 51 mm thick. Made of steel plate welded inside and outside become one entity and contains a protective layer CS350.

Door

: 74 mm thick. Consists of a protective layer Solid Steel Plates 8 mm thick. Locking and home fireproof Panel thickness of 15 mm at the rear door. In the locking area is equipped with a drill-resistant steel plate and around the door is equipped with a "Fire Seal" which will expand and close the gap between the door and body in the event of a fire.

Kev


: Sargent & Greenleaf combination lock (S & G, made in USA) 1,000,000 variation 3 wheel with code. Certification: UL Group 2, Vds Class 1, CEN A. Mauer key lock key (Made in Germany) 8 lever double bit. Certification: UL 437, Vds Class 1, EN 1300A.

Locking System

: Reinforced doors to the body with a diameter of 22 mm Steel Bolt on the front side and dogging bar on the side of the hinge that provides protection if the hinges are cut or damaged so that the door will not open.


Dimension

Fireproof [0000 Burglarproof [0000



HOME SAFE 270

Height / External	: 372 mm
Width	: 472 mm
Depth	: 393 mm
Height / Internal	: 270 mm
Width	: 370 mm
Depth	: 260 mm
Handle High	: 50 mm
Locking Bolts	: 2 pcs
Capacity	: 26 Liters
Net Weight	: 120 kgs



HOME SAFE 370

Height / External	: 472 mm
Width	: 372 mm
Depth	: 393 mm
Height / Internal	: 370 mm
Width	: 270 mm
Depth	: 260 mm
Handle High	: 50 mm
Locking Bolts	: 2 pcs
Capacity	: 26 Liter
Net Weight	: 120 kgs



- Body
- : 85 mm thick. Made of steel plate welded inside and outside become one entity and contains a protective layer of CS 350.
- Door
- $90\,$ mm thick. Made of solid steel plate protective layer $10\,$ mm thick, fire-resistant panels as thick as 15 mm in the rear doors and locking the house. In the locking area is equipped with a drill-resistant steel plate and equipped with fire around the door seal for protection against fire.
- Key
- Sargent & Greenleaf combination (S & G, made in USA) 1,000,000 variation 3 wheel with code. Certification: UL Group 2, Vds Class 1, CEN A.
- Mauer key lock key (Made in Germany) 8 lever double bit. Certification: UL 437, Vds Class 1, EN 1300A.

Locking System

Reinforced doors to the body with a 28 mm diameter steel bolt on the front side and dogging bar on the side of the hinge that provides protection if the hinges are cut or damaged so that the door will not open.

Dimension


Fireproof **II**000 Burglarproof [[0]



•	CHALLENGER 1
Height / External	: 641 mm
Width	: 551 mm
Depth	: 495 mm
Height / Internal	: 481 mm
Width	: 381 mm
Depth	: 320 mm
Handle High	: 50 mm
Locking Bolts	: 2 pcs
Capacity	: 58 Liters
Net Weight	: 280 kgs



LHAL	LENGER Z
Height / External	: 790 mm
Width	: 551 mm
Depth	: 495 mm
Height / Internal	: 630 mm
Width	: 381 mm
Depth	: 320 mm
Handle High	: 50 mm
Locking Bolts	: 3 pcs
Capacity	: 77 Liters
Net Weight	: 340 kgs



Net Weight

CHALLENGED 3

: 460 kgs

	ALLLINGLIN 3
Height / External	: 790 mm
Width	: 670 mm
Depth	: 585 mm
Height / Internal	: 630 mm
Width	: 500 mm
Depth	: 410 mm
Handle High	: 50 mm
Locking Bolts	: 3 pcs



L		CHALLE	NGE	K 4
١	Height / External Width Depth	:	1000 670 585	mm
١	Height / Internal Width Depth	: :	840 500 410	mn
l (Handle High Locking Bolts Capacity Net Weight	: : :	4 172 L	mn pcs iter kg:



Specification



Body

: 100 mm thick. Made of steel plate inside and outside the CS 350 contains a protective layer bonded to the body with a special anchoring system.

170 mm thick. Consists of a protective layer of 85 mm thick CS 350. In the locking area is equipped with a drill-resistant steel plate and 1 piece of automatic safety lock behind. Around the door is equipped with a fire seal for protection against fire.

Sargent & Greenleaf combination lock (S & G, made in USA) 1,000,000 variation 3 wheel with code. Equipped with "Spy Proof Ring". Certification: UL Group 2, Vds Class 1, CEN A.

Mauer key lock key (Made in Germany) 8 lever double bit. Certification: UL 437, Vds Class 1, EN 1300A.

Locking System

Door

Key

Reinforced doors to the body with a 38 mm diameter steel bolt on the front side, top & bottom and dogging bar on the side of the hinge that provides protection if the hinges are cut or damaged so that the door will not open.

Dimension

Fireproof [] [] [] Burglarproof IIII00



Height / Internal

Width

Depth

Width

Depth

Handle High

Locking Bolts

Capacity

Net Weight



: 614 mm

: 477 mm

: 381 mm

: 340 mm

· 50 mm

: 4 pcs

: 62 Liters

: 425 kgs

P	RO	ТΙ	FC^{-}	$T \cap$	R	•
	110				٠.	

Height / External	: 830 mm
Width	: 650 mm
Depth	: 704 mm
Height / Internal	: 630 mm
Width	: 450 mm
Depth	: 430 mm
Handle High	: 50 mm
Locking Bolts	: 5 pcs
Capacity	: 122 Liter
Net Weight	: 590 kgs



Height / External

Height / Internal Width

Width

Depth

Depth

Handle High

Locking Bolts

Capacity

Net Weight

PROTECTO

TECTOR 3		PROCTECTOR 4
: 1130 mm	Height / External	: 1470 mm
: 650 mm	Width	: 740 mm
: 704 mm	Depth	: 823 mm
: 930 mm	Height / Internal	: 1250 mm
: 450 mm	Width	: 520 mm
: 430 mm	Depth	: 530 mm
: 50 mm	Handle High	: 50 mm
: 6 pcs	Locking Bolts	: 9 pcs
: 180 Liters	Capacity	: 344 Liters
: 780 kgs	Net Weight	: 1340 kgs



Specification



Body

Door

Kev

Locking

System

- : 110 mm thick. Made of steel plate welded inside and outside become one unit and CS 500 contains a protective layer bonded to the body with a special anchoring system.
- : 180 thick. Consists of a protective layer of 95 mm thick CS 500. In the locking area is equipped with a drill-resistant steel plate and 2 automatic safety behind the combination lock and key lock. Around the door is equipped with a fire seal for protection against fire.
- : Sargent & Greenleaf combination lock (S & G, made in USA) 4 wheels with 100,000,000 variations of code that comes with "Spy Proof Ring" and "Check Dial Lock". Certification: UL Group 2, Vds Class 2, CEN B.

Mauer key lock key (Made in Germany) 8 lever double bit. Certification: UL 437, Vds Class 1, EN 1300A.

Reinforced doors to the body with a 3-way moving bolt system diameter 38 mm on the front side, top & bottom and dogging bar on the side of the hinge that provides protection if the hinges are cut or damaged so that the door will not open.

Dimension

Fireproof IIIII Burglarproof **IIII**



Height / Externa

Net Weight



: 1210 kgs

	CONQUEROR
l	: 1200 mm

Width	: 740 mm
Depth	: 820 mm
Height / Internal	: 980 mm
Width	: 520 mm
Depth	: 530 mm
Handle High	: 50 mm
Locking Bolts	: 8 pcs
Capacity	: 271 Liters



0 0	CONQUEROR 2
Height / External	: 1470 mm
Width	: 740 mm
Depth	: 820 mm
Height / Internal	: 1250 mm
Width	: 520 mm
Depth	: 530 mm
Handle High	: 50 mm
Locking Bolts	: 9 pcs
Capacity	: 344 Liter
Net Weight	: 1430 kg



CONQUEROR 3

- T	-
Height / External	: 1700 mm
Width	: 740 mm
Depth	: 820 mm
Height / Internal	: 1480 mm
Width	: 520 mm
Depth	: 530 mm
Handle High	: 50 mm
Locking Bolts	: 10 pcs
Capacity	: 408 Liters
Net Weight	: 1600 kgs



	CONQUEROR 2
Height / External Width Depth	: 1700 mm : 990 mm : 820 mm
Height / Internal Width Depth	: 1480 mm : 770 mm : 530 mm
Handle High Locking Bolts	: 50 mm
Capacity Net Weight	: 604 Liter : 1990 kg

Specification CHAMPION



Body : 110 thick. Made of steel plate welded inside and outside into a single unit containing Alloy Cast Hard protective coatings and protective coatings Cassa CS 500, which is fastened to the body with a special anchoring system. Construction body specially designed to be difficult to get into the room fire in

a closet in the event of a fire.

: 191 thick. Hard protective coating consists of Cast Alloy, CS 500 and 95 mm thick fire-resistant panels behind doors as thick as 16 mm. Around the door is equipped with a fire seal for protection against fire.

Sargent & Greenleaf combination lock (S & G, made in USA) 4 wheels with 100,000,000 variations of code that comes with "Spy Proof Ring" and "Check Dial Lock". Certification: UL Group 2, Vds Class 2, CEN B.

Mauer key lock key (Made in Germany) 8 lever double bit. Certification: UL 437, Vds Class 1, EN 1300A.

Locking : Reinforced doors to the body with 4-way moving bolt system diameter 38 mm on the left, right, top and bottom.

Fireproof | | | | | | Burglarproof !!!!!

Dimension



CHAMPION 1

Height / External	: 1200 mm
Width	: 740 mm
Depth	: 820 mm
Height / Internal	: 980 mm
Width	: 520 mm
Depth	: 515 mm
Handle High	: 50 mm
Locking Bolts	: 12 pcs
Capacity	: 262 Liters
Net Weight	: 1520 kgs



CHAMPION 2

Door

Key

System

Height / External	: 1470 mm
Width	: 740 mm
Depth	: 820 mm
Height / Internal	: 1250 mm
Width	: 520 mm
Depth	: 515 mm
Handle High	: 50 mm
Locking Bolts	: 14 pcs
Capacity	: 335 Liters
Net Weight	: 1810 kgs



CHAMPION 3

Height / External	: 1700 mm
Width	: 740 mm
Depth	: 820 mm
Height / Internal	: 1480 mm
Width	: 520 mm
Depth	: 515 mm
Handle High	: 50 mm
Locking Bolts	: 16 pcs
Capacity	: 396 Liters
Net Weight	: 2040 kgs



CHAMPION 4

Height / External	: 1700 mm
Width	: 990 mm
Depth	: 820 mm
Height / Internal	: 1480 mm
Width	: 770 mm
Depth	: 515 mm
Handle High	: 50 mm
Locking Bolts	: 16 pcs
Capacity	: 587 Liters
Net Weight	: 2520 kgs

Specification



: 98 mm thick. Made of steel plate welded inside and outside into a single unit containing refractory lining DS 950 is fastened to the body with a special anchoring system. Around the door is equipped with a fire seal for protection

Door

: 84 mm thick. Made of steel plate welded inside and outside thoroughly into one and contains lapihan fireproof DS 950.

Key

Sargent & Greenleaf combination lock (S & G, made in USA) 1,000,000 variation 3 wheel with code. Certification: UL Group 2, Vds Class 1, CEN A.

Mauer key lock key (Made in Germany) 8 lever double bit. Certification: UL 437, Vds Class 1, EN 1300A.

Drawer

: Each drawer in the Document Safe is equipped with a drawer lock. Each drawer can be drawn in full and can be loaded with a hanging folder so as to facilitate rapid search through a drawer.

Fireproof | | | | | | Burglarproof **III** 00

Dimension



Net Weight

DS 2 LACI

: 375 kgs

	D3 Z LACI
Height / External	: 772 mm
Width	: 621 mm
Depth	: 800 mm
Height / Internal	: 240 mm
Width	: 385 mm
Depth	: 578 mm
Handle High	: 50 mm
Locking Bolts	: 4 pcs



DS 3 LACI

Height / External	: 1067 mm
Width	: 621 mm
Depth	: 800 mm
Height / Internal	: 240 mm
Width	: 385 mm
Depth	: 578 mm
Handle High	: 50 mm
Locking Bolts	: 6 pcs
Capacity	: 160 Liter
Net Weight	: 490 kg



DS 4 LACI

Height / External	: 1362 mm
Width	: 621 mn
Depth	: 800 mn
Height / Internal	: 240 mn
Width	: 385 mn
Depth	: 578 mn
Handle High	: 50 mn
Locking Bolts	: 8 pc:
Capacity	: 214 Liter
Net Weight	: 600 kg

STALLENKAST

Specification



Board : 81 mm thick. Made of steel inner and outer plate welded into a single unit and contains "Fireproof Coatings DS 950" is tied to the body with a special anchoring system. Around the door is equipped with a "Fire Seal" which will expand and

close the gap between the door and body, in the event of a fire.

: 104 mm thick. Made of steel plate welded inside and outside the whole into a

single entity and containing "DS Fire Resistant Coatings 950" as thick as 44 mm.

: Sargent & Greenleaf combination lock (S & G, made in USA) 1,000,000 variation

3 wheel with code. Certification: UL Group 2, Vds Class 1, CEN A.

Mauer key lock key (Made in Germany) 8 lever double bit. Certification: UL 437,

Mauer key lock key (Made in Germany) 8 lever double bit. Certification: UL 437, Vds Class 1, EN 1300A.

Locking System

Door

Key


Reinforced doors to the body with a 25 mm diameter steel bolt on the front side, top & bottom and dogging bar on the side of the hinge that provides protection if the hinges are cut or damaged so that the door will not open.

Adjustable shelves

: Each door is equipped with a double stallenkast 3 (three) pieces of shelves that can be adjusted in accordance with the wishes of the user.

Fireproof Burglarproof Bull 00

Dimension



STALLENKAST DOUBLE DOOR

· 1742 mm Height / External : 1000 mm Width : 535 mm Depth Height / Internal : 1580 mm Width 898 mm Depth 380 mm Handle high 50 mm Locking Bolt 12 pcs Internal Volume : 539 litres

500 kgs

DOCUMENT SAFE BPKB

Specification

Body

Door

Kev

Locking

System

Drawer

Net Weight



- : 98 mm thick. Made of steel plate welded inside and outside into a single unit containing refractory lining DS 950 is fastened to the body with a special anchoring system. Around the door is equipped with a fire seal for protection against fire.
- : 84 mm thick. Made of steel plate welded inside and outside thoroughly into one and contains lapihan fireproof DS 950.
- : Sargent & Greenleaf combination lock (S & G, made in USA) 1,000,000 variation 3 wheel with code. Certification: UL Group 2, Vds Class 1, CEN A.

Mauer key lock key (Made in Germany) 8 lever double bit. Certification: UL 437, Vds Class 1, EN 1300A.


: 3 Direction + dogging Bar. Reinforced doors to the body with a 25 mm diameter steel bolt on the front side, top & bottom and dogging bar on the side of the hinge that provides protection if the hinges are cut or damaged so that the door will not open.

: Each drawer in the Document Safe is equipped with a drawer lock. Each drawer can be drawn in full and can be loaded with a hanging folder so as to facilitate rapid search through a drawer.

Fireproof Burglarproof

Dimension

DS 7 IACI 2 LAJUR



 Height / External
 : 1364 mm

 Width
 : 621 mm

 Depth
 : 800 mm

 Height / Internal
 : 1145 mm

 Width
 : 436 mm

Depth : 603 mm

BPKB Storage Capacity : 2730 BPKB
Net Weight : 600 kgs



DS 10 LACI 2 LAJUR

: 1820 mm Height / External Width 621 mm 800 mm Depth Height / Internal : 1635 mm Width 436 mm 603 mm Depth **BPKB Storage Capacity** : 3900 BPKB : 1000 kgs Net Weight



DS 10 LACI 3 LAJUR

Net Weight

Width Depth	: 776 mm : 800 mm
Height / Internal Width Depth	: 1635 mm : 436 mm : 603 mm
RPKR Storage Canacity	· 5850 BPKE

: 1200 kgs

Deposit System

Specification CASH TRAP CHALLENGER

: Money put into a cash trap. At the time the trap is closed cas then money will automatically fall into the safe. The money is already in the safe can not be lured or crocheted with a hook tool as a cash trap opened the access to the inside of the safe will automatically be

85 mm thick. Made of steel plate welded inside and outside become

90 mm thick. Made of solid steel plate protective layer 10 mm thick,

one entity and contains a protective layer of CS 350.



Body

Doors

Kev


fire-resistant panels as thick as 15 mm in the rear doors and locking the house. In the locking fitted dengtan drill resistant steel plate and equipped with fire around the door seal for protection against fire.


Sargent & Greenleaf combination lock (S & G, made in USA) 1,000,000 variation 3 wheel with code. Certification: UL Group 2, Vds Class 1, CEN A

Mauer key lock key (Made in Germany) 8 lever double bit. Certification: UL 437, Vds Class 1, EN 1300A.

1 Direction + dogging Bar. Reinforced doors to the body with a 28 mm diameter steel bolt on the front side and dogging bar on the side of the hinge that provides protection if the hinges are cut or damaged so that the door will not open.

Dimension





Locking System




CASH TRAP 1

: 641 mm Height / External Width : 551 mm Depth : 495 mm : 481 mm Height / Internal Width 381 mm : 320 mm Depth Handle High 50 mm **Locking Bolts** 2 pcs Net Weight 280 kgs



CASH TRAP 2

Height / External	: 790 mm
Width	: 551 mm
Depth	: 495 mm
Height / Internal	: 630 mm
Width	: 381 mm
Depth	: 320 mm
Handle High	: 50 mm
Locking Bolts	: 3 pcs
Net Weight	: 340 kgs




CASH TRAP 3

Height / External : 790 mm Width : 670 mm Depth : 585 mm : 630 mm Height / Internal Width : 500 mm : 410 mm Depth Handle High 50 mm Locking Bolts 3 pcs Net Weight 460 kgs

covered by the flap.

covered by the flap



CASH TRAP 4

Height / External	: 1000 mm
Width	: 670 mm
Depth	: 585 mm
Height / Internal	: 840 mm
Width	: 500 mm
Depth	: 410 mm
Handle High	: 50 mm
Locking Bolts	: 4 pcs
Net Weight	: 570 kgs

Specification

Deposit System

DRAWER TRAP (

: Money put into a cash trap. At the time the trap is closed cas then money will automatically fall into the safe. The money is already in the safe can not be lured or crocheted with a hook tool as a cash trap opened the access to the inside of the safe will automatically be

: 85 mm thick. Made of steel plate welded inside and outside become

: 90 mm thick. Made of solid steel plate protective layer 10 mm thick,

fire-resistant panels as thick as 15 mm in the rear doors and locking the house. In the locking fitted dengtan drill resistant steel plate and equipped with fire around the door seal for protection against fire.

one entity and contains a protective layer of CS 350.



Body

Doors

Key

Locking

System

Fireproof [] [] [] Burglarproof **III**

Sargent & Greenleaf combination lock (S & G, made in USA) 1,000,000 variation 3 wheel with code. Certification: UL Group 2, Vds Class 1,

Mauer key lock key (Made in Germany) 8 lever double bit. Certification: UL 437, Vds Class 1, EN 1300A.


: 1 Direction + dogging Bar. Reinforced doors to the body with a 28 mm diameter steel bolt on the front side and dogging bar on the side of the hinge that provides protection if the hinges are cut or damaged so that the door will not open.








Net Weight



360 kgs



DRAWER TRAP 2

Height / External	:1000 mm
Width	: 551 mm
Depth	: 495 mm
Height / Internal	: 630 mm
Width	: 381 mm
Depth	: 320 mm
Handle High	: 50 mm
Locking Bolts	: 3 pcs
Net Weight	: 420 kgs




Net Weight

DRAWER TRAP 3

560 kgs

Height / External	: 1000 mm
Width	: 670 mm
Depth	: 585 mm
Height / Internal	: 630 mm
Width	: 500 mm
Depth	: 410 mm
Handle High	: 50 mm
Locking Bolts	: 3 pcs



DRAWER TRAP 4

Height / External	: 1210 mm
Width	: 670 mm
Depth	: 585 mm
Height / Internal	: 630 mm
Width	: 500 mm
Depth	: 410 mm
Handle high	: 50 mm
Locking Bolts	: 3 pcs
Net Weight	: 670 kg

Why CASSA?



Each CASSA coated fire safe door seal. When the fire seals exposed to heat, it expands, thus closing the gap between the wall and the door safes. This prevents the hot air into the safe through the gap.




Safe CASSA is protected by a hard-alloy casting special plate, which has a high resistance over drilling and oxy-acetylene welding. Safe CASSA also coated high quality steel which has high resistance to bending provide which moment. maximum protection demolition



MAX-SECURITY LOCKS

CASSA only use the best We keywords. use a combination lock brands S&G Americans high-precision and double-bit key lock brands Mauer of Germany which is not easily duplicated.



Reinforced with relocking device system in case of forcible demolition blasting, then 2 pieces behind the automatic safety lock combination will work automatically and the door remains locked even if two keys have been open.

Testing of Fire Resistant Safe Certificate

Fuel Safe has been tested for 2 hours with a temperature of 922.6 ° C, and the temperature in the safe convey only 104.1 ° C, while the maximum allowable temperature is 177 ° C.

CASSA proven product quality is the best.

SERTIFIKAT PENGUJIAN

The CASSA Safe

Secure Combination Lock, USA

We use the highest grade combination locks available to ensure maximum reliability and security. Made in USA.



Secure Digital Lock, USA

We offer an optional UL Listed Type 1 digital lock. The digital lock comes with one master code, eight user codes, and a penalty time feature to prevent opening by entering random codes until a valid code is found. The lock can be programmed to open with a 9-minutes time delay. Made in USA.



8 Lever Double Bit Key Lock, Germany

A secondary key lock comes with every CASSA Safe to provide a second layer of access control. Due to our key's geometry, it can only be duplicated with special tooling and highly trained personnels. Made in Germany.




Fire Seal, Australia

Every CASSA safe is lined with a fire seal that expands to seal the gap between the door and the body in the event of a fire. Made in Australia.



Re-locking Mechanism

A re-locking mechanism detects any forced attempts to open the safe by drilling or torch-welding and engages a permanent locking system.





TESTIMONIAL

PT FEDERAL INTERNATIONAL FINANCE

" With this we say that the products of PT Pertiwi Agung Persindo we use the Document Safe brand CASSA type DS7 has a good quality it has been tested in the fires of our branch office on March 13, 2011.

In the event the entire building and its contents were burned, including the safe document. Once the fire is out, we were worried that we document can not be saved anymore, apparently after his condition really cool and we open the safe document of our documents are in good condition without any damage.

So that we can deliver, with the above incident we are more confident and believe in the quality of goods produced CASSA. "

Vivi Andriani, General Services Dept. Head

FACT FIRE INCIDENT

Date of Incident : March 13, 2011

Type Safes : Document Safe DS-7 Laci Khusus BPKB

Doods are stored in a safe : 5.600 BPKB





PT RAMAYANA LESTARI SENTOSA, Tbk

"In connection with a fire at one of our stores in the mall Department Ciledug Tangerang on the 11th of November 2014 in which iron lebari CASSA Brands that we use to save money from the sale were also burned.

Once the vault is successful we open 2 days later, we found money and other items stored in the cabinets are all still intact as before.

With the above incident, we believe and are sure top quality brands CASSA vault.

We gratefully acknowledge the assistance and services that have been provided. "

Hin Tjoeng, Head of Public



FACT FIRE INCIDENT

Date of Incident : November 11, 2004

Type Safes : Brankas CASSA type Conqueror size 2

Doods are stored in a safe : Money and Documents

PT SINAR GAJAH PERMAI

"We would like to thank PT. Persindo Pertiwi Agung due vault size Conqueror brand CASSA type 2 that we bought had saved money and important documents that we hold didalamnnya of fire accident.

Given these events, we feel confident and do not hesitate on excellence and strength of the brand CASSA vault.

Once again we would like to thank you for the help and services that have been given at the time of the incident. $\mbox{"}$

Marwin, Director

FACT FIRE INCIDENT

Date of Incident Type Safes Doods are stored in a safe : November 24, 2001

: Brankas CASSA type Conqueror size 2

: Money and Documents

